



## Mercury Vapor Removal Adsorbent

---

### Product Information

Hg-A® is a pelleted, steam activated carbon which has been sulphur impregnated for removal of mercury vapor from natural gas and hydrogen streams. This product is available in 3mm, 4mm and 6 mm diameter pellets, and in special particle sizes tailored for specific applications. Product packaging is available in 275 lbs steel drums, on pallets of four drums per pallet, in 50 lb sacks, and in 1,100 lb supersacks.

### Applications

Hg-A is designed to remove mercury vapor from air, hydrogen, natural gas, and other gas streams. Hg-A has proven its capacity for mercury and ability to achieve less than 0.1 PPB (V) (1µg/Nm³) mercury vapor effluent concentrations in commercial installations.

For recommendations on your specific application, call SME Process Solution, (281) 440-7350

For price and shipment information contact your Area Sales Representative:

### SME Process Solution

6715 Theall  
Houston, TX 77066  
Phone (281)440-7350  
Fax (281)440-7353  
www.sme-llc.com

Information presented herein is believed to be accurate and reliable but does not imply any guarantee or warranty. Nothing herein shall be construed as an invitation to use processes covered by patents without proper arrangements with individuals or companies owning those patents.

## Hg-A Adsorbent: Typical Properties

---

### Physical Properties

---

Surface area, base carbon N <sub>2</sub> BET (ASTM D2854)	1,000 m <sup>2</sup> /gm, minimum
Hardness (ASTM D3802)	97%
Sulphur content	13 – 14 weight %
Moisture content (ASTM D2867)	3 weight %,
Packed bulk density	37 lbs/ft <sup>3</sup> (590 kg/m <sup>3</sup> )

### Chemical Properties

---

Carbon tetrachloride activity, Base carbon(ASTM D3467)	60 weight %, typical
PH (ASTM D3838)	6 – 8
Actual mercury capacity to 99% removal from H <sub>2</sub>	65 weight %
Recommended adsorption contact time, at <70%RH	10 seconds
Effluent mercury concentration	<0.01 PPB (V) (<.01µg/Nm <sup>3</sup> )

---

**CAUTION: OXYGEN IS REMOVED FROM AIR BY WET ACTIVATED CARBON. ASPHYXIATION HAZARD EXISTS INSIDE VESSELS.**

---

## SME Process Solution

6715 Theall  
Houston, TX 77066  
Ph (281) 440-7350 Fax (281) 440-7353